

V_{DSS} , 24V R_{DS(ON)} , 7.7 mΩ (max.) @ V_{GS}=4.5V R_{DS(ON)} , 7.9 mΩ (max.) @ V_{GS}=4.0V R_{DS(ON)} , 8.8 mΩ (max.) @ V_{GS}=3.1V R_{DS(ON)} , 9.8 mΩ (max.) @ V_{GS}=2.5V I_D , 13A	DFN 3x3-8L	

Description	Features
The SG2402TD uses advanced trench technology to provide excellent R _{DS(ON)} , low gate charge and operation with gate voltages as low as 1.8V. This device is suitable for use as a load switch or in PWM applications. It is ESD protected.	<ul style="list-style-type: none"> Low On-Resistance ESD Protection Pb-free lead plating; RoHS compliant
	Applications
	<ul style="list-style-type: none"> Load Switch Battery Powered Systems

Ordering Information

Ordering Code	RoHS Status	Package	Package Code	Packing	Quantity
SG2402TD	Halogen-Free	DFN 3x3-8L	TD	Tape & Reel	3,000

Absolute Maximum Ratings (T_A=25°C unless otherwise noted)

Parameter		Symbol	Value	Unit
Drain-Source Voltage		V _{DS}	24	V
Gate-Source Voltage		V _{GS}	±12	V
Drain Current-Continuous	T _A =25°C	I _D	13	A
Drain Current-Pulsed ^{Note 1}		I _{DM}	54	A
Maximum Power Dissipation	Mounted on ceramic substrate (900mm ² x 0.8mm) 1 unit	P _D	2.7	W
	Mounted on ceramic substrate (900mm ² x 0.8mm)	P _T	2.7	W
Operating Junction Temperature Range		T _J T _{STG}	-55 to +150	°C

Thermal Resistance Ratings

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Maximum Junction-to-Ambient ^{Note 1}	R _{θJA}	Steady State	-	-	59	°C/W
Maximum Junction-to-Case	R _{θJC}	Steady State	-	-	1.4	°C/W

Notes:

- Pulse Test: Pulse Width ≤ 10μs, Duty Cycle ≤ 1%.
- Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Electrical Characteristics (T_J=25°C unless otherwise noted)


OFF CHARACTERISTICS						
Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _{DS} =250μA	24	27.5	-	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =20V, V _{GS} =0V	-	-	1	μA
Gate-Body Leakage	I _{GSS}	V _{GS} =±8V, V _{DS} =0V	-	-	±5	μA

ON CHARACTERISTICS						
Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _{DS} =250μA	0.45	0.6	1.3	V
Drain -Source On -State Resistance	R _{DS(ON)}	V _{GS} =4.5V, I _{DS} =5.5A	-	6.7	7.7	mΩ
		V _{GS} =4.0V, I _{DS} =5.5A	-	6.9	7.9	
		V _{GS} =3.1V, I _{DS} =5.5A	-	7.5	8.8	
		V _{GS} =2.5V, I _{DS} =3.0A	-	8.2	9.8	

SWITCHING CHARACTERISTICS						
Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Turn-On Delay Time	T _{d(on)}	V _{DD} =10V, I _{DS} =7A, V _{GS} =4.5V, R _g =1kΩ See Switching Time Test Circuit	-	0.56	-	μs
Rise Time	t _r		-	0.54	-	
Turn-Off Delay Time	T _{d(off)}		-	19	-	
Fall Time	t _f		-	22	-	
Total Gate Charge at 4.5V	Q _g	V _{DS} =10V, I _{DS} =13A, V _{GS} =4.5V	-	13.2	-	nC
Gate to Source Gate Charge	Q _{gs}		-	3.1	-	
Gate to Drain "Miller" Charge	Q _{gd}		-	2.4	-	


DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS						
Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Drain-Source Diode Forward Voltage	V _{SD}	V _{GS} =0V, I _{DS} =13A	-	0.7	1.2	V

Switching Time Test Circuit




Typical Operating Characteristics


Output Characteristics




Gate Threshold Voltage




Gate-Source On Resistance




Drain-Source On Resistance



Drain-Source On Resistance




Source-Drain Diode Forward




Typical Operating Characteristics (Cont.)


Power Dissipation




Drain Current



Safe Operation Area




Gate Charge



Package Dimensions


Package type: DFN3x3-8L

T-TYPE




Symbol	Min	Nor	Max
A	0.70	0.75	0.80
b	0.25	0.30	0.35
c	0.15	0.20	0.25
D	2.90	3.00	3.10
E	2.90	3.00	3.10
e	0.65 BSC		
L	0.37	0.51	0.65
b1	0.45	0.50	0.55
E1	1.625	1.725	1.825
D1	2.20	2.30	2.40
e1	0.425	0.525	0.625

S-TYPE



1. All dimension are in millimeters.
2. Dimension dose not include burrs and mold flash/protrusions.


Land pattern (Footprint)



Soldering Methods for Silicongear's Products

1. Storage environment: Temperature=10°C to 35°C Humidity=65%±15%
2. Reflow soldering of surface-mount devices

Figure 1: Temperature profile



Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Average ramp-up rate (TL to TP)	<3°C/sec	<3°C/sec
Preheat		
- Temperature Min (Tsmin)	100°C	150°C
- Temperature Max (Tsmax)	150°C	200°C
- Time (min to max) (ts)	60 to 120 sec	60 to 180 sec
Tsmax to TL		
- Ramp-up Rate	<3°C/sec	<3°C/sec
Time maintained above:		
- Temperature (TL)	183°C	217°C
- Time (tL)	60 to 150 sec	60 to 150 sec
Peak Temperature (TP)	240°C +0/-5°C	260°C +0/-5°C
Time within 5°C of actual Peak Temperature (tP)	10 to 30 sec	20 to 40 sec
Ramp-down Rate	<6°C/sec	<6°C/sec
Time 25°C to Peak Temperature	<6 minutes	<8 minutes

3. Flow (wave) soldering (solder dipping)

Products	Peak Temperature	Dipping Time
Pb devices.	245°C ±5°C	5sec ±1sec
Pb-Free devices.	260°C +0/-5°C	5sec ±1sec

Important Notice

© Silicongear Corporation

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Silicongear cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in an Silicongear product. No circuit patent licenses, copyrights, mask work rights, or other intellectual property rights are implied.

Silicongear Corporation, its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Silicongear"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Silicongear makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Silicongear disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Silicongear's knowledge of typical requirements that are often placed on Silicongear products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Silicongear's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Silicongear products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Silicongear product could result in personal injury or death. Customers using or selling Silicongear products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Silicongear and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Silicongear or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Silicongear personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Silicongear. Product names and markings noted herein may be trademarks of their respective owners.

Silicongear and the Silicongear logo are trademarks of Silicongear Corporation. All other brand and product names appearing in this document are registered trademarks or trademarks of their respective holders.